

SRS Biolub synth 68



Synthetic chainsaw oil

April 2013

Characteristics

SRS Biolub synth 68 is an environmentally friendly, synthetic and biodegradable chainsaw oil.

The use of toxicologically safe, synthetic esters ensures good environmental compatibility (water contaminating class = 1).

SRS Biolub synth 68 has very good adhesion and lubrication properties as well as high wear and corrosion protection.

Application

SRS Biolub synth 68 is universally applicable for all types of chainsaws, even at extremely low outdoor temperatures in winter (up to -30°C). It is very stable to oxidation, special additives prevent resins and adhesions, even during prolonged operating interruptions.

Performance / Specifications

SRS Biolub synth 68 is biodegradable according to OECD 301 F (manometric respiration test).

SRS Biolub synth 68 is certified by the German Army and under the B-0389 qualification certificate according to the specification TL 9150-0089, part 3; Bw-Code OY1180; approved.

SRS Biolub synth 68 is a product of the H&R ChemPharm GmbH.

Typical Data		Test method	SRS Biolub synth 68
Colour		DIN ISO 2049	L 1,0
Density at 15°C	g/cm ³	DIN 51 757	0.935
Kin. Viscosity at 40°C	mm ² /s	DIN EN ISO 3104	68
Kin. Viscosity at 100°C	mm ² /s	DIN EN ISO 3104	12.7
Flash Point COC	°C	DIN ISO 2592	306
Pour Point	°C	DIN ISO 3016	< - 40
Neutralization Number	mgKOH/g	DIN 51 558	0.7
Copper Corrosion (3 h, 100°C)	grade	DIN EN ISO 2160	1b
Seel Corrosion	Grade	DIN ISO 7120	0

The above values may vary within the commercial limits.

Made in Germany