

SRS Mihagrun LA 40



Gas Engine Oil

February 2015

Characteristics

SRS Mihagrun LA 40 gas engine oil is manufactured for use in gas-powered spark ignition engines. It is recommended for gas engines which are subject to higher thermal stresses and which can not be dealt with by ash-free gas engine oils. It is also qualified for use in gas engines operating on low sulphur natural and refinery gases, propane, butane, and propane / butane blends.

Application

SRS Mihagrun LA 40 corresponds to the requirements of leading gas engine manufacturers and is also suitable for operation with catalytic converters

Performance / Specifications

- SAE Grade 40
- API CF

Approvals / Recommendations

- MWM/Caterpillar Approval TR 0199-99-2105
- Deutz Approval TR 0199-99-01213/1 DE
- MTU Approval MTL 5074 gas engines
- MAN M 3271-2
- GE Jenbacher
- Waukesha

SRS Mihagrun LA 40 gas engine oil is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Mihagrun LA 40
SAE Grade	SAE J 300	40
Density at 15°C	DIN 51 757	0.891
Kin. Viscosity at 40°C	DIN EN ISO 3104	147
Kin. Viscosity at 100°C	DIN EN ISO 3104	14.3
Flash Point COC	DIN ISO 2592	280
Pour Point	DIN ISO 3016	-21
Total Base Number	DIN ISO 3771	5.6
Sulphated Ash	DIN 51 575	0.48

The above values may vary within the commercial limits.

Made in Germany